

FloorBridge® Finish

2-component, quick-setting sealer

Areas of Application

Sealer for FloorBridge joint profiles, for indoor and outdoor use.

Advantages

- 2-component
- polyaspartic
- UV-resistant
- moisture tolerant
- plasticizer-free
- chemical resistant
- hydrolysis resistant
- de-icing salt resistant
- alkali-resistant
- glossy finish

Product Data

Packaging/Color

transparent: 1 kg kneading bag in plastic container

Comp. A: 1,87 kg

Comp. B: 625 g

Color RAL 7001: 2,5 kg kneading bag in plastic container

Comp. A: 620 g

Comp. B: 380 g

each incl. 2 paint rollers

Technical Data

Application time

approx. 20 minutes

Rainproof

colored: approx. 45 minutes

transparent: approx. 60 minutes



Overcoating / walkable

colored: after approx. 6 hours

transparent: after approx. 2 hours

Loadable

colored: after approx. 12 hours

transparent: after approx. 6 hours

Overcoating

within 12 hours

Consumption

approx. 250 – 500 g/m²

Mixing ratio

color: 3:1 in parts by weight

transparent: 1,63:1 in parts by weight

Solvent content

colored: solvent-free

transparent: low-solvent

Application Conditions / Limitations

Substrate Temperature

+ 5°C up to + 30°C

Ambient Temperature

+ 5°C up to + 30°C

Material Temperature

+ 5°C up to + 30°C

Application

Substrate preparation and conditions

The substrate must be clean, dust-free, dry, fine textured and load bearing. It must be dense enough and of sufficient strength, free of separating substances, oil, fat etc. The overcoating times between layers must be observed.

Application

The mixed sealer is applied to the substrate and evenly spreaded. Avoid roller marks. To achieve a seamless finish, the entire surface must be finished in one application step without interruption. To avoid colour differences, it is important to use packages with the same batch-number.

Mixing

Mix hardener component B and base component A homogenously and streak-free for a minimum of 3 minutes. Then pour the mixture into a clean container and mix again with a stirrer at 300 rounds / min. for a minimum of 1 minute.

Cleaning of tools

Cleaning of tools possible with commercially available cleaners for reactive resins.

Curing Conditions

Notes

Time-information given above can be shorter at higher temperatures and can be longer at lower temperatures. Application tools and equipment used, and different site conditions have an influence at the given consumption rates. They therefore can change. Surface Irregularities and unevenness in the substrate cannot be levelled with this product. Don't mix and apply the product with non-system products. Do not use other materials than those recommended by FloorBridge. All technical values given are based on results determined at + 20°C and at a relative humidity of 50 %. Due to weather influences like wind, humidity or temperature, the declared values can change accordingly.

Safety Information

Important Safety Information

For detailed information refer to the most recent Safety Data Sheet at <http://www.floorbridge.com>.

Storage conditions / Shelf Life

Store the original packaging between +5°C and 30°C in dry conditions.

Duration of storage: 12 months from date of production. Avoid direct sun light, also during application.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of FloorBridge® products, are given in good faith based on the current knowledge and experience of FloorBridge® International GmbH about the products, and apply if properly stored, handled and under normal conditions in accordance with FloorBridge® International GmbH recommendations.

In practice, the differences in materials, substrates and deviating working conditions are so substantial, that FloorBridge® International GmbH shall neither accept any warranty nor liability for a particular merchantability or suitability for a particular purpose, neither derived from this information nor from a written recommendation or any other advice offered. The user of the product must verify the product's suitability for the intended purpose of use. FloorBridge® International GmbH reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to final confirmation and subject to our current terms and conditions regarding sales and deliveries.

Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of FloorBridge® International GmbH.