

Declaration of Performance / DoP	
Acc. Annex III of the Regulation (EU) Nr. 305/2011 Construction Products Regulation	
FloorBridge SM 150 / 200 / 400 / 700	
1. Unique identification code of the product-type:	33/V.01
2. Type-, batch- or serial number or a different label for the identification of the building product acc. to article 11 par. 4:	see packaging of the product
3. Intended use:	TPE waterproofing membrane for building waterproofing against soil moisture and water Moisture barrier type A Groundwater barrier type T
4. Manufacturer:	FloorBridge International Gewerbepark 21 4101 Feldkirchen an der Donau
5. Where appropriate, name and contact address of the authorized representative, mandated with the tasks acc. article 12 par. 2	not relevant
6. System (s) for assessment and verification of constancy of performance of the building product	System 2+ System 4
7. Harmonized standard: Notified body:	EN 13967:2012 ZA.1 MPA Braunschweig, 0761
8. European technical assessment:	not relevant



9. Declared performance (s):

EN 13967:2012 ZA.1		EN 13967:2012
Fire performance	Class E	
Watertightness	60 kPa / 24 Std.: passed 400 kPa 72 Std.: passed	
Resistance of shock loads	≥ 250 mm	
Durability of waterproofing against artificial aging	60 kPa / 24 Std.: passed	
Durability of waterproofing against chemicals	60 kPa / 24 Std.: passed	
Tear resistance (nail shaft)	lengthwise: ≥ 100 N across: ≥ 100 N	
Shear resistance of the joint seams	≥ 160 N/50mm	
Resistance to static load	Procedure A: EPS plate ≥ 10 kg passed Procedure B: concrete ≥ 15 kg passed	
Tensile strength	lengthwise: ≥ 7,3 N/mm ² across: ≥ 6,7 N/mm ² lengthwise: ≥ 450 % across: ≥ 450 %	
Dangerous substances	NPD	

10. The performance of the product identified in numbers 1 and 2 is in conformity with the set of declared performances in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in number 4.

Signed for and on behalf of the manufacturer by:

Feldkirchen, 27.07.2022

place and date of issue

Ing. Lisa Enzenberger

product manager / technical manager





0761

FloorBridge International GmbH, Gewerbepark 21, 4101 Feldkirchen an der Donau

2022

33/V.01

EN 13967:2012

Waterproofing membrane for building waterproofing against oil, moisture and water
EN 13967:2012 ZA.1

Fire performance	Class E
Watertightness	60 kPa / 24 Std.: passed 400 kPa 72 Std.: passed
Resistance of shock loads	≥ 250 mm
Durability of waterproofing against artificial aging	60 kPa / 24 Std.: passed
Durability of waterproofing against chemicals	60 kPa / 24 Std.: passed
Tear resistance (nail shaft)	lengthwise: ≥ 100 N across: ≥ 100 N
Shear resistance of the joint seams	≥ 160 N/50mm
Resistance to static load	Procedure A: EPS plate ≥ 10 kg passed Procedure B: concrete ≥ 15 kg passed
Tensile strength	lengthwise: ≥ 7,3 N/mm ² across: ≥ 6,7 N/mm ² lengthwise: ≥ 450 % across: ≥ 450 %



FloorBridge®



Carbon Composite Joint Profiles

floorbridge.com

