

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

FloorBridge Connect 04, Part A

UFI: J3T0-CGF4-UQE5-VQ78

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Chemical product for construction and industry.

For use in industrial installations and professional treatment only.

##### Uses advised against

The product is not intended for private use.

#### 1.3. Details of the supplier of the safety data sheet

Company name: FloorBridge International GmbH  
 Street: Gewerbepark 21  
 Place: A-4101 Feldkirchen a.d. Donau  
 Telephone: +43 664 88182991  
 E-mail: stefan.trichlin@floorbridge.com  
 Internet: http://www.floorbridge.com

#### 1.4. Emergency telephone number: +49(0)4941-60436-0 (Mo - Fr 08:00 - 17:00 h (CET))

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No 1272/2008

Skin Irrit. 2; H315  
 Eye Irrit. 2; H319  
 Skin Sens. 1; H317  
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

##### Regulation (EC) No 1272/2008

##### Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane  
 Bis(4,4'-glycidylloxyphenyl)-methane  
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.  
 Diglycidyl ether of polypropylene glycol

Signal word: Warning

Pictograms:



##### Hazard statements

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P391 Collect spillage.

##### Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### 2.3. Other hazards

No further relevant information available.

### SECTION 3: Composition/information on ingredients

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 2 of 10

**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			10 - < 25 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
-	Bis(4,4'-glycidylloxyphenyl)-methane			5 - < 10 %
	701-263-0		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.			5 - < 10 %
	271-846-8	603-103-00-4	01-2119485289-22	
	Skin Irrit. 2, Skin Sens. 1; H315 H317			
26142-30-3	Diglycidyl ether of polypropylene glycol			1 - < 5 %
	-			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
13463-67-7	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			0 - < 1 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	10 - < 25 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 15000 mg/kg Skin Irrit. 2; H315: ≥ 5 - 100 Eye Irrit. 2; H319: ≥ 5 - 100	
-	701-263-0	Bis(4,4'-glycidylloxyphenyl)-methane	5 - < 10 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
68609-97-2	271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	5 - < 10 %
		dermal: LD50 = > 10000 mg/kg	
26142-30-3	-	Diglycidyl ether of polypropylene glycol	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 4000 mg/kg	

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

Remove affected person from the danger area and lay down. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunk in little sips (dilution effect). Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic reactions

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 3 of 10

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO<sub>2</sub>)
- Dry extinguishing powder

#### Unsuitable extinguishing media

- Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide
- Nitrogen oxides (NO<sub>x</sub>)

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear personal protection equipment (refer to section 8). Safe handling: see section 7.

Provide adequate ventilation.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Clean contaminated articles and floor according to the environmental legislation. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal.

### 6.4. Reference to other sections

Personal protection equipment: see section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Use personal protection equipment.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

#### Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Use protective skin cream before handling the product. Remove contaminated, saturated clothing immediately. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

#### Further information on handling

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area. Street clothing should be stored separately from work clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container. Protect from direct sunlight.

#### Hints on joint storage

Keep away from: Food and feedingstuffs

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 4 of 10

### Further information on storage conditions

Protect against:

- Frost
- Humidity
- Heat

### 7.3. Specific end use(s)

No data available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
13463-67-7	Titanium dioxide, respirable dust	-	4		TWA (8 h)	

#### DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Consumer DNEL, acute		oral	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m³
-	Bis(4,4'-glycidylloxyphenyl)-methane			
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m³
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m³
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.			
Consumer DNEL, long-term		oral	systemic	1 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	1219 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	10 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	17 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	2,35 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	3,9 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	7,6 mg/m³
Worker DNEL, acute		inhalation	systemic	29 mg/m³
Consumer DNEL, long-term		inhalation	systemic	4,1 mg/m³
Worker DNEL, long-term		inhalation	systemic	13,8 mg/m³
Consumer DNEL, acute		inhalation	local	2,9 mg/m³
Worker DNEL, acute		inhalation	local	9,8 mg/m³
Consumer DNEL, long-term		inhalation	local	1,46 mg/m³
Worker DNEL, long-term		inhalation	local	0,98 mg/m³

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 5 of 10

### PNEC values

CAS No	Substance	
Environmental compartment		Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater		0,006 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,341 mg/kg
Marine sediment		0,034 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,065 mg/kg
-	Bis(4,4'-glycidylloxyphenyl)-methane	
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,029 mg/kg
Soil		0,237 mg/kg
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	
Freshwater		0,0072 mg/l
Marine water		0,00072 mg/l
Freshwater sediment		66,77 mg/kg
Marine sediment		6,677 mg/kg
Soil		80,12 mg/kg

### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: Eye glasses with side protection  
spray application: Wear face protection.

##### Hand protection

Suitable material:  
- NBR (Nitrile rubber)  
- Butyl caoutchouc (butyl rubber)  
DIN-/EN-Norms DIN-/EN-Norms EN ISO 374

Use gloves only once. Replace when worn. Use protective skin cream before handling the product.

##### Skin protection

Wear suitable protective clothing and gloves.  
The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.  
spray application: Chemical protection clothing.

##### Respiratory protection

Usually no personal respirative protection necessary. In case of inadequate ventilation wear respiratory protection.  
spray application: Use appropriate respiratory protection.

##### Environmental exposure controls

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	thixotropic	
Colour:	various	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:	No data available	No data available

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 6 of 10

Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	> 95 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic:	No data available
Water solubility:	slightly soluble
Solubility in other solvents:	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Density (at 23 °C):	~ 1,6 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

### 9.2. Other information

#### Other safety characteristics

Viscosity / dynamic: thixotropic

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Reaction with:

- Amines
- Acid
- Alkali (lye)

### 10.4. Conditions to avoid

No data available

### 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

No data available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 mg/kg	15000	Rat	
	dermal	LD50 mg/kg	23000	Rabbit	
-	Bis(4,4'-glycidylloxyphenyl)-methane				
	oral	LD50 mg/kg	> 5000	Rat	
	dermal	LD50 mg/kg	> 2000	Rat	
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.				
	dermal	LD50 mg/kg	> 10000	Rat	
26142-30-3	Diglycidyl ether of polypropylene glycol				
	oral	LD50 mg/kg	> 4000	Rat	
	dermal	LD50 mg/kg	> 2000	Rat	

### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

### Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxy)phenyl]propane; Bis(4,4'-glycidylloxyphenyl)-methane; oxirane, mono[(C12-14-alkyloxy)methyl] derivs.; Diglycidyl ether of polypropylene glycol)

Contains epoxy constituents. May produce an allergic reaction.

May cause heavy allergic reactions with chronic effects after a sensitization and a later exposure by very low amounts.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute fish toxicity	LC50	2,0 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	11 mg/l	72 h	Algae	
	Acute crustacea toxicity	EC50	1,8 mg/l	48 h	Daphnia magna (Big water flea)	
-	Bis(4,4'-glycidylloxyphenyl)-methane					
	Acute fish toxicity	LC50	2,54 mg/l	96 h		
	Acute algae toxicity	ErC50	1,8 mg/l	72 h		
	Acute crustacea toxicity	EC50	2,55 mg/l	48 h	Daphnia magna (Big water flea)	
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.					
	Acute fish toxicity	LC50	> 1 - 10 mg/l	96 h	Leuciscus idus (golden orfe)	
	Acute crustacea toxicity	EC50	> 1 - 10 mg/l	48 h	Daphnia magna (Big water flea)	

### 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No further relevant information available.

### Further information

Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. The waste code has to be identified in agreement with the disposal company or the competent authority.

#### Contaminated packaging

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

#### 14.1. UN number or ID number:

UN 3082

#### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)

#### 14.3. Transport hazard class(es):

9

#### 14.4. Packing group:

III

Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 9 of 10

### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 3082
<b>14.2. UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	9
<b>14.4. Packing group:</b>	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 3082
<b>14.2. UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	9
<b>14.4. Packing group:</b>	III
Hazard label:	9
Marine pollutant:	yes
Special Provisions:	274 335 969
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-F

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 3082
<b>14.2. UN proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<b>14.3. Transport hazard class(es):</b>	9
<b>14.4. Packing group:</b>	III
Hazard label:	9
Special Provisions:	A97 A158 A197 A215
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	epoxy resin

### 14.6. Special precautions for user

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: < 500 g/l (A+B)

Subcategory according to Directive 2004/42/EC:

Two-pack reactive performance coatings for specific end use such as floors - Solvent-borne coatings, VOC limit value: 500 g/l

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## FloorBridge Connect 04, Part A

Revision date: 14.06.2024

Page 10 of 10

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,12,14,16.

#### Abbreviations and acronyms

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Carc: Carcinogenicity

Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### Further Information

The amendments made by COMMISSION REGULATION (EU) 2020/878 have been taken into account in this safety data sheet.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*