

Declaration of Performance / DoP	
Acc. Annex III of the Regulation (EU) Nr. 305/2011 Construction Products Regulation	
FloorBridge Epoxy mortar 300	
1. Unique identification code of the product-type:	163/V.01
2. Type-, batch- or serial number or a different label for the identification of the building product acc. to article 11 par. 4:	see packaging of the product
3. Intended use:	synthetic resin screed for indoor applications
4. Manufacturer:	FloorBridge International Gewerbepark 21 4101 Feldkirchen an der Donau
5. Where appropriate, name and contact address of the authorized representative, mandated with the tasks acc. article 12 par. 2	not relevant
6. System (s) for assessment and verification of constancy of performance of the building product	System 4 System 4
7. Harmonized standard: Notified body:	EN 13813:2002 ZA 1.5 -
8. European technical assessment:	not relevant



9. Declared performance (s):

EN 13813:2002 ZA.15		EN 13813:2002
Reaction to fire (for not covered layers)	Class E _{fl}	
Release of corrosive substances	SR	
Permeability to water	NPD	
Mechanical resistance Wear resistance (of the wearing layers)	≤ AR 1 or A6	
Mechanical resistance Bonding strength	≥ B1,5	
Mechanical resistance impact resistance (of the wearing layers)	≥ IR4	
Footfall sound insulation	NPD	
Sound absorption	NPD	
Thermal insulation	NPD	
Chemical resistance	NPD	
Dangerous substances	NPD	

10. The performance of the product identified in numbers 1 and 2 is in conformity with the set of declared performances in number 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in number 4.

Signed for and on behalf of the manufacturer by:


Feldkirchen, 23.12.2022

place and date of issue

Ing. Lisa Enzenberger

product manager / technical manager



	
FloorBridge International GmbH, Gewerbepark 21, 4101 Feldkirchen an der Donau	
2022	
163/V.01	
EN 13813:2002	
Synthetic resin screed for indoor applications EN 13813:2002 ZA.15	
Reaction to fire (for not covered layers)	E _{fl}
Release of corrosive substances	SR
Mechanical resistance Wear resistance (of the wearing layers)	≤ AR 1 or A6
Mechanical resistance Bonding strength	≥ B1,5
Mechanical resistance Impact resistance (of the wearing layers)	≥ IR4

