

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **FloorBridge Epoxy 300 Comp. B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

FloorBridge International GmbH
Gewerbepark 21
A-4101 Feldkirchen a. d. Donau

Information department:

+43 7233 200 30
office@floorbridge.com

1.4 Emergency telephone number: during usual office-times: +43 7233 200 30

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

| | |
|-------------------|---|
| Acute Tox. 4 | H302 Harmful if swallowed. |
| Skin Corr. 1 | H314 Causes severe skin burns and eye damage. |
| Eye Dam. 1 | H318 Causes serious eye damage. |
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| Repr. 2 | H361f Suspected of damaging fertility. |
| Aquatic Chronic 2 | H411 Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

paraformaldehyde, polymeric reaction products with 4-tert.-butylphenol, mphenylenebis(methylamine) and trimethylhexane-1,6-diamine
3-aminomethyl-3,5,5-trimethylcyclohexylamine
4-tert-butylphenol
m-phenylenebis(methylamine)
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
N-(3-(trimethoxysilyl)propyl)ethylenediamine
2-piperazin-1-ylethylamine
triethylenetetramine

Hazard statements

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P391 Collect spillage.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

| Dangerous components [% w/w]: | | |
|---|---|----------|
| | paraformaldehyde, polymeric reaction products with 4-tert.-butylphenol, mphenylenebis(methylamine) and trimethylhexane-1,6-diamine Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥25-<30% |
| CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX | benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332 | ≥10-<20% |
| CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX | 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 % | ≥10-<20% |
| CAS: 98-54-4 EINECS: 202-679-0 Reg.nr.: 01-2119489419-21-XXXX | 4-tert-butylphenol Repr. 2, H361f; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315 | ≥10-<20% |
| CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX | m-phenylenebis(methylamine) Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071 | ≥10-<20% |
| CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX | 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317 | ≥5-<10% |
| CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27-XXXX | 2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302 | ≥2.5-<3% |
| CAS: 103-83-3 EINECS: 203-149-1 Index number: 612-074-00-7 Reg.nr.: 01-2119529232-48-XXXX | benzyl dimethylamine Flam. Liq. 3, H226; Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412 | ≥1-<2.5% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 2)

| | | |
|--|--|----------|
| CAS: 1760-24-3 EINECS: 217-164-6 | N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317 | ≥0.5-<1% |
| CAS: 140-31-8 EINECS: 205-411-0 Index number: 612-105-00-4 Reg.nr.: 01-2119471486-30-XXXX | 2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥0.5-<1% |
| CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4 Reg.nr.: 01-2119473798-17-XXXX | Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335 | ≥0.5-<1% |
| CAS: 90640-67-8 EINECS: 292-588-2 Index number: 612-059-00-5 Reg.nr.: 01-2119487919-13-XXXX | triethylenetetramine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥0.5-<1% |

SVHC

CAS: 98-54-4 | 4-tert-butylphenol

Additional information For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Coughing

Dazed

Respiratory distressn (dyspnoea)

Gastro-intestinal symptoms

nausea

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

carbon monoxides

further harmful conflagration gases and fumes

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 3)

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Use only in well ventilated areas.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:**

Store only in unopened original containers.

Prevent any penetration into the ground.

Information on storage in a common storage facility:

Store away from oxidising agents.

Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 4)

site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Filter A/P2.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

| | |
|---|----------------------------------|
| Physical state | Fluid |
| Colour: | Clear |
| Odour: | Amine-like |
| Odour threshold: | Not determined. |
| Melting point/freezing point: | Not determined |
| Boiling point or initial boiling point and boiling range | Not determined |
| Flammability | Not applicable. |
| Lower and upper explosion limit | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Flash point: | 106 °C (Setaflash) |
| Ignition temperature: | not applicable |
| Decomposition temperature: | Not determined. |
| pH at 20 °C | 11 |
| Viscosity: | |
| Kinematic viscosity | Not determined. |
| dynamic at 20 °C: | 0.97 mPas |
| Solubility | |
| Water: | Not miscible or difficult to mix |
| Partition coefficient n-octanol/water (log value) | Not determined. |
| Vapour pressure: | Not determined. |
| Density and/or relative density | |
| Density at 20 °C: | 1.02 g/cm ³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |

9.2 Other information

Appearance:

Form: Fluid

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 5)

| | |
|--|---------------------------|
| Important information on protection of health and environment, and on safety. | |
| Explosive properties: | Product is not explosive. |
| Solvent separation test | < 3 % |
| Change in condition | |
| Evaporation rate | Not determined. |
| Information with regard to physical hazard classes | |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flammable gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |
| Organic peroxides | Void |
| Corrosive to metals | Void |
| Desensitised explosives | Void |

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Harmful if swallowed.

| | | |
|--|------|-----------------------|
| LD/LC50 values that are relevant for classification: | | |
| CAS: 100-51-6 benzyl alcohol | | |
| Oral | LD50 | 1,620 mg/kg (rat) |
| Dermal | LD50 | >2,000 mg/kg (rabbit) |
| CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine | | |
| Oral | LD50 | 1,030 mg/kg (ATE) |
| | | 1,030 mg/kg (rat) |
| Dermal | LD50 | 1,840 mg/kg (rabbit) |
| CAS: 98-54-4 4-tert-butylphenol | | |
| Oral | LD50 | 2,951 mg/kg (rat) |
| Dermal | LD50 | 2,288 mg/kg (rabbit) |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 6)

| | | |
|---|------|-----------------------|
| CAS: 1477-55-0 m-phenylenebis(methylamine) | | |
| Oral | LD50 | 930 mg/kg (rat) |
| Dermal | LD50 | >3,100 mg/kg (rabbit) |

Skin corrosion/irritation: Causes severe skin burns and eye damage.**Serious eye damage/irritation:** Causes serious eye damage.**Sensitisation:** May cause an allergic skin reaction.**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Suspected of damaging fertility.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.**Aspiration hazard:** Based on available data, the classification criteria are not met.**11.2 Information on other hazards**

| |
|--|
| Endocrine disrupting properties |
| None of the ingredients is listed. |

* **SECTION 12: Ecological information****12.1 Toxicity**

| |
|---|
| Aquatic toxicity: |
| CAS: 1477-55-0 m-phenylenebis(methylamine) |
| EC50/48h 15.2 mg/l (Daphnia magna) |

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects**Remark:** Toxic for fish**Additional ecological information:****General notes:**

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

* **SECTION 13: Disposal considerations****Recommendation**

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

| |
|---|
| European waste catalogue |
| 20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27 |

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

* **SECTION 14: Transport information**

| | |
|------------------------------------|--------|
| 14.1 UN number or ID number | |
| ADR, IMDG, IATA | UN2735 |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 7)

| | |
|---|---|
| 14.2 UN proper shipping name ADR IMDG, IATA | 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) |
| 14.3 Transport hazard class(es) ADR  Class Label | 8 (C7) Corrosive substances. 8 |
| IMDG, IATA  Class Label | 8 Corrosive substances. 8 |
| 14.4 Packing group ADR, IMDG, IATA | II |
| 14.5 Environmental hazards: Marine pollutant: | Not applicable. - |
| 14.6 Special precautions for user hazard identification number: EMS Number: Segregation groups Stowage Category Segregation Code | Warning: Corrosive substances. 88 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| Transport/Additional information: | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code Remarks: | 0 Code: E0 Not permitted as Excepted Quantity 1 E No subject to the regulations of the ADR when transported in the original container/carton according to chapter 3.4 (transport in limited quantities). |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) Remarks: | 0 Code: E0 Not permitted as Excepted Quantity No subject to the regulations of the IMDG when transported in the original container/carton according to chapter 3.4 (transport in limited quantities). |
| UN "Model Regulation": | UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE)), 8, II |

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

| |
|---|
| DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II |
|---|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| |
|----------------------------------|
| REGULATION (EU) 2019/1148 |
|----------------------------------|

| |
|---|
| Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)) |
|---|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

| |
|--|
| Annex II - REPORTABLE EXPLOSIVES PRECURSORS |
|--|

| |
|------------------------------------|
| None of the ingredients is listed. |
|------------------------------------|

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

| |
|---|
| Substances of very high concern (SVHC) according to UK REACH |
|---|

| |
|-----------------------------------|
| CAS: 98-54-4 4-tert-butylphenol |
|-----------------------------------|

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H311 Toxic in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H361f Suspected of damaging fertility.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 14.11.2022

Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.02.2023

Version number 2 (replaces version 1)

Revision: 23.02.2023

Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3