

## Safety data sheet according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

### \* SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name FloorBridge Epoxy 300 Comp. B****UFI:** H8UD-724D-F60F-V7WV

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture** Coating

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

FloorBridge International GmbH

Gewerbepark 21

A-4101 Feldkirchen a. d. Donau

**Information department:**

+43 7233 200 30

office@floorbridge.com

**1.4 Emergency telephone number:** during usual office-times: +43 7233 200 30

### \* SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4	H302 Harmful if swallowed.
Skin Corr. 1	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Repr. 2	H361f Suspected of damaging fertility.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS05 GHS07 GHS08 GHS09

**Signal word** Danger**Hazard-determining components of labelling:**

paraformaldehyde, polymeric reaction products with 4-tert.-butylphenol, m-phenylenebis(methylamine) and trimethylhexane-1,6-diamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4-tert-butylphenol

m-phenylenebis(methylamine)

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

N-(3-(trimethoxysilyl)propyl)ethylenediamine

2-piperazin-1-ylethylamine

3,6-diazaoctanethylenediamin

**Hazard statements**

H302 Harmful if swallowed.

(Contd. on page 2)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 1)

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P391 Collect spillage.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.**vPvB:** Not applicable.

#### Determination of endocrine-disrupting properties

CAS: 98-54-4 4-tert-butylphenol

List I

### \* SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

#### Dangerous components [% w/w]:

CAS: 158800-93-2	Formaldehyde, reaction products with 1,3-benzenedimethanamine and p-tert-butylphenol Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 4, H413 ATE: LD50 oral: 500 mg/kg LD50 dermal: 1,100 mg/kg	≥25-<30%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1B, H317 ATE: LD50 oral: 1,200 mg/kg	≥10-<20%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥10-<20%
CAS: 98-54-4 EINECS: 202-679-0 Reg.nr.: 01-2119489419-21-XXXX	4-tert-butylphenol Repr. 2, H361f; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Skin Irrit. 2, H315	≥10-<20%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071	≥10-<20%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥5-<10%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥2-<3%

(Contd. on page 3)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 2)

CAS: 103-83-3 EINECS: 203-149-1 Index number: 612-074-00-7 Reg.nr.: 01-2119529232-48-XXXX	benzylidimethylamine Flam. Liq. 3, H226; Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	≥1-<2%
CAS: 1760-24-3 EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318; Skin Sens. 1B, H317; STOT SE 3, H335	≥0.5-<1%
CAS: 140-31-8 EINECS: 205-411-0 Index number: 612-105-00-4 Reg.nr.: 01-2119471486-30-XXXX	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.5-<1%
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4 Reg.nr.: 01-2119473798-17-XXXX	Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335 ATE: LD50 oral: 500 mg/kg	≥0.5-<1%
CAS: 90640-67-8 EINECS: 292-588-2 Index number: 612-059-00-5 Reg.nr.: 01-2119487919-13-XXXX	3,6-diazaoctanethylenediamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.5-<1%

### SVHC

CAS: 98-54-4 4-tert-butylphenol

**Additional information** For the wording of the listed hazard phrases refer to section 16.

## \* SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

#### After skin contact

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

**After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

#### After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Coughing

Dazed

Respiratory distressn (dyspnoea)

Gastro-intestinal symptoms

nausea

### 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

## \* SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents** Use fire fighting measures that suit the environment.

**For safety reasons unsuitable extinguishing agents** not relevant

### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

# Safety data sheet

## according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

### Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 3)

May be released in case of fire  
 Carbon monoxide (CO)  
 Carbon dioxide  
 carbon monoxides  
 further harmful conflagration gases and fumes

#### **5.3 Advice for firefighters**

##### **Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

##### **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## \* **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

### **6.2 Environmental precautions:**

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

### **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

### **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling** Use only in well ventilated areas.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Storage**

##### **Requirements to be met by storerooms and containers:**

Store only in unopened original containers.

Prevent any penetration into the ground.

##### **Information on storage in a common storage facility:**

Store away from oxidising agents.

Store away from food.

##### **Further information about storage conditions:**

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

### **7.3 Specific end use(s)** not relevant

## \* **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

**Additional information:** The lists that were valid during compilation were used as a basis.

### **8.2 Exposure controls**

**Appropriate engineering controls** No further data; see section 7.

#### **Individual protection measures, such as personal protective equipment**

##### **General protective and hygienic measures**

Do not eat, drink or smoke while working.

(Contd. on page 5)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 4)

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

### **Respiratory equipment:**

Filter A/P2.

Only use ambient air independent respiratory equipment in pits, shafts and silos!

### **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### **Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.

**Body protection:** Protective work clothing.

### **Environmental exposure controls**

Use suitable containers to avoid contamination of the environment. Prevent from entering the sewage system or into surface and ground water. Information on limiting and monitoring environmental exposure can be found in section 6 can be found in section 6.

## \* **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

#### **General Information**

##### **Physical state**

Liquid

##### **Colour:**

Clear

##### **Odour:**

Amine-like

##### **Odour threshold:**

Not determined.

##### **Melting point/freezing point:**

Not determined

##### **Boiling point or initial boiling point and boiling range**

Not determined

##### **Flammability**

Not applicable.

##### **Lower and upper explosion limit**

Not determined.

##### **Lower:**

Not determined.

##### **Upper:**

Not determined.

##### **Flash point:**

106 °C (Setaflash)

##### **Auto-ignition temperature:**

not applicable

##### **Decomposition temperature:**

Not determined.

##### **pH at 20 °C**

11

##### **Viscosity:**

Not determined.

##### **Kinematic viscosity**

0.97 mPas

##### **dynamic at 20 °C:**

##### **Solubility**

Not miscible or difficult to mix

(Contd. on page 6)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 5)

<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.02 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Explosive properties:</b>	Product is not explosive.
<b>Solvent separation test</b>	< 3 %
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No further relevant information available.

### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

### 10.3 Possibility of hazardous reactions

No dangerous reactions known

### 10.4 Conditions to avoid

No further relevant information available.

### 10.5 Incompatible materials:

No further relevant information available.

### 10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity:** Harmful if swallowed.

#### LD/LC50 values that are relevant for classification:

**CAS: 158800-93-2 Formaldehyde, reaction products with 1,3-benzenedimethanamine and p-tert-butylphenol**

Oral	LD50	500 mg/kg (ATE)
------	------	-----------------

(Contd. on page 7)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 6)

Dermal	LD50	1,100 mg/kg (ATE)
<b>CAS: 100-51-6 benzyl alcohol</b>		
Oral	LD50	1,200 mg/kg (ATE) 1,620 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
<b>CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>		
Oral	LD50	1,030 mg/kg (ATE) 1,030 mg/kg (rat)
<b>CAS: 98-54-4 4-tert-butylphenol</b>		
Oral	LD50	2,951 mg/kg (rat)
Dermal	LD50	2,288 mg/kg (rabbit)
<b>CAS: 1477-55-0 m-phenylenebis(methylamine)</b>		
Oral	LD50	930 mg/kg (rat)
Dermal	LD50	>3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
<b>CAS: 25513-64-8 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine</b>		
Oral	LD50	910 mg/kg (rat)
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Oral	LD50	2,169 mg/kg (rat)
<b>CAS: 103-83-3 benzylidemethylamine</b>		
Oral	LD50	265 mg/kg (rat)
Dermal	LD50	1,660 mg/kg (rabbit)
Inhalative	LC50/4 h	2.06 mg/l (rat) mg/l (rabbit)
<b>CAS: 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine</b>		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
<b>CAS: 140-31-8 2-piperazin-1-ylethylamine</b>		
Oral	LD50	2,140 mg/kg (rat)
Dermal	LD50	866 mg/kg (rabbit)
<b>CAS: 61788-46-3 Amines, coco alkyl</b>		
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	>2,000 mg/kg (rat)
<b>CAS: 90640-67-8 3,6-diazaoctanethylenediamine</b>		
Oral	LD50	1,716 mg/kg (rat)
Dermal	LD50	1,465 mg/kg (rabbit)

**Specific symptoms in animal assay:**

**Skin corrosion/irritation:** Causes severe skin burns and eye damage.

**Serious eye damage/irritation:** Causes serious eye damage.

**Sensitisation:** May cause an allergic skin reaction.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Suspected of damaging fertility.

**STOT-single exposure:** Based on available data, the classification criteria are not met.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### 3 Endocrine disrupting properties

CAS: 98-54-4	4-tert-butylphenol	List I
--------------	--------------------	--------

(Contd. on page 8)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 7)

### \* **SECTION 12: Ecological information**

#### 12.1 Toxicity

##### Aquatic toxicity:

**CAS: 1477-55-0 m-phenylenebis(methylamine)**

EC50/48h 15.2 mg/l (Daphnia magna)

**CAS: 90640-67-8 3,6-diazaoctanethylenediamin**

EC50/48h 31.1 mg/l (Daphnia magna)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

#### 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects** No further relevant information available.

**Remark:** Toxic for fish

#### Additional ecological information:

##### General notes:

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

### \* **SECTION 13: Disposal considerations**

#### 13.1 Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

#### Uncleaned packaging:

##### Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

### \* **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR, IMDG, IATA

UN2735

#### 14.2 UN proper shipping name

ADR

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(m-phenylenebis(methylamine))

IMDG, IATA

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))

#### 14.3 Transport hazard class(es)

ADR



Class

8 (C7) Corrosive substances.

(Contd. on page 9)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

**Trade name FloorBridge Epoxy 300 Comp. B**

(Contd. of page 8)

<b>Label</b>	8
<b>IMDG, IATA</b>	
	
<b>Class</b>	8 Corrosive substances.
<b>Label</b>	8
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	II
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>Marine pollutant:</b>	-
<b>14.6 Special precautions for user</b>	Warning: Corrosive substances.
<b>hazard identification number:</b>	88
<b>EMS Number:</b>	F-A,S-B
<b>Segregation groups</b>	(SGG18) Alkalies
<b>Stowage Category</b>	A
<b>Segregation Code</b>	SG35 Stow "separated from" SGG1-acids
<b>14.7 Maritime transport in bulk according to</b>	
<b>IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	E
<b>Remarks:</b>	No subject to the regulations of the ADR when transported in the original container/carton according to chapter 3.4 (transport in limited quantities).
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
<b>Remarks:</b>	No subject to the regulations of the IMDG when transported in the original container/carton according to chapter 3.4 (transport in limited quantities).
<b>UN "Model Regulation":</b>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE)), 8, II

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poisons Act**

<b>Regulated explosives precursors</b>
None of the ingredients is listed.
<b>Regulated poisons</b>
None of the ingredients is listed.
<b>Reportable explosives precursors</b>
None of the ingredients is listed.
<b>Reportable poisons</b>
None of the ingredients is listed.

(Contd. on page 10)

**Safety data sheet**  
according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name **FloorBridge Epoxy 300 Comp. B**

(Contd. of page 9)

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category E2** Hazardous to the Aquatic Environment**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)**

None of the ingredients is listed.

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**National regulations****Other regulations, limitations and prohibition ordinances**

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

**Substances of very high concern (SVHC) according to UK REACH**

CAS: 98-54-4 4-tert-butylphenol

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Delivery specifications are found in the respective Technical Information Sheets.

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH071 Corrosive to the respiratory tract.

**Classification according to Regulation (EC) No 1272/2008**

Calculation method

On basis of test data

Acute toxicity - oral  
Skin corrosion/irritation  
Serious eye damage/irritation  
Skin sensitisation  
Reproductive toxicity  
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 11)

# Safety data sheet

according to UK REACH

Printing date 06.02.2026

Version number 3 (replaces version 2)

Revision: 06.02.2026

## Trade name FloorBridge Epoxy 300 Comp. B

(Contd. of page 10)

**Department issuing data specification sheet:** Product Safety department / EHS

**Date of previous version:** 14.11.2022

**Version number of previous version:** 2

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

### \* Data compared to the previous version altered.

This document replaces all previous versions. The information in this safety data sheet corresponds to our current state of knowledge and complies with national and EU legislation. However, the given working conditions of the user are beyond our knowledge and control. The product must not be used for purposes other than those specified in section 1 without written authorization. The user is responsible for compliance with all necessary legal regulations. The information in this safety data sheet describes the safety requirements of our product and does not constitute a guarantee of product properties. We accept no liability for errors in the printed form.